

LED P+ 100

CLASS
1

IP 54

3m
H07RN-F
(3G 1,5 mm²)
NEOPRENE

16A + T

ON/OFF
SWITCH50-100%
SWITCH2x USB
connectionENERGY
SAVING


P. 509

9000
LumenLED P+100
SMD LED TECHNOLOGY
100W


NEW




ALL-IN-ONE

COLOR
TEMPERATURE
SELECTION

6500 °K



4500 °K



2700 °K

LED P+100 "HIGH POWER" straler
LED P+100 "HAUTE PUISSANCE"

code



€

mm

LM 33600



5420000063273

100 W

368 x 346 x 92

4,254 kg

80

4

1

127,00

LED P-80

CLASS
1

IP 54

3m
H07RN-F
(3G 1,5 mm²)
NEOPRENE

16A + T

ON/OFF
SWITCHENERGY
SAVING

4000 °K



P. 509

6800
LumenLED P-80
SMD LED TECHNOLOGY
80WLED P-80 "HIGH POWER" straler
LED P-80 "HAUTE PUISSANCE"PRIJSDALING
CHUTE DE PRIX

code



€

mm

LM 33580



5420000042483

80 W

342 x 295 x 112

1,125 kg

48

4

1

99,50

LED LB-50

CLASS
1

IP 54

5m
H07RN-F
(3G 1,5 mm²)
NEOPRENE

16A + T

ON/OFF
SWITCHENERGY
SAVING

6000 °K



P. 509

LED LB-50
SMD LED TECHNOLOGY
50W4000
Lumen

LED LB-50 Power worklight 360° • LED LB-50 Power worklight 360°

code



€

mm

LM 37500



5420000062153

50 W

280 x 286 x 280

2,600 kg

40

4

1

80,70